

MATERIAL SAFETY DATA SHEET**IDENTIFICATION AND COMPANY**

Trade Name	EVERFLUX
Type & Product/Use	Water Soluble Soldering Flux
Company	The Wiseman Group Manufacturing Chemists P.O Box 58 High Street INGATESTONE Essex CM4 9DL Tel: 01277-633200

COMPOSITION

Fatty Esters	
Surfactants	< 5% w/w
Emulsifying Oils	
Soluble Waxes	
Ammonium Chloride	> 2% w/w
Zinc Chloride	> 4% w/w
White Oils	
Inhibitors	< 2% w/w

HAZARD IDENTIFICATION

Zinc Chloride:	CAS No 7646-85-7	TLV (units) 1 mg/m ³
Ammonium Chloride	CAS No 12125-02-9	TLV (units) 10 mg/m ³

THIS PRODUCT IS NOT CLASSIFIED ACCORDING TO THE CHEMICALS HAZARD INFORMATION AND PACKAGING FOR SUPPLY (AMENDMENT) REGULATIONS 1996.

FIRST AID MEASURES

SKIN: Contact should be avoided. Prolonged or repeated contact with the skin can inflame, irritate and burn the skin. In case of skin contact, immediate washing with plenty of soap and water is recommended.

EYES: Contact should be avoided. If this occurs, irrigate for at least 15 minutes under running cold tap and seek medical attention.

INHALATION: Remove to fresh air. If recovery is not immediate call doctor at once.

INGESTION: DO NOT INDUCE VOMITING. Drink Bicarbonate of Soda in water/milk/Milk of Magnesia or Washing Soda in water. Call Doctor immediately.

FIRE FIGHTING MEASURES

This product is water based and would not support combustion.

ACCIDENTAL RELEASE

In the event of spillage mop up bulk and dilute remainder to foul drain with water. Treat large spillages as industrial waste.

HANDLING AND STORAGE

Store in original containers and protect from extremes of temperature. Do not mix with any other material other than water as directed.

