

MONUMENT TOOLS LTD 2330N 2331Q 2332T 2333W 2334Z GLASS FIBRE YARN			
HEALTH & SAFETY - COSHH		Issue number :	1
Date :	19 November 2001 (11:46:04)	Page :	1 of 1
Prepared by :	Safety Unit	Approved by :	Managing Director

### MATERIAL SAFETY DATA SHEET

Product Code :	2330N, 2331Q, 2332T, 2333W, 2334Z
Product Description :	Glass Fibre Yarn
Product Name:	Pyroseal PGS.10

#### GENERAL PRECAUTIONS

SKIN:	Some people handling the glass fibre for the first time , or after a period of absence from contact, may experience skin irritation. This is usually a temporary phenomenon which subsides as skin hardens naturally
-------	--

#### PERCAUTIONS

SKIN:	Irritation can be minimised by rinsing the skin under cold or lukewarm water before washing in a proprietary brand antiseptic soap. This method prevents the pores opening and allowing the glass fibres to penetrate and cause further irritation. A good quality barrier cream should be used on all occasions before commencing work.
CLOTHING:	Operative who have continual exposure find it best to wear loose clothing avoiding tight constriction around the neck and wrist and we recommend that work clothing should be washed separately from the family clothing

#### SPECIFICATION

OPERATING TEMP:	<600°C
-----------------	--------

**PYROSEAL PGS. 10** is ideal for use in dry, static sealing applications involving hot air and combustion gases.